


WEATHERHEAD HYDRAULIC
HIGH PRESSURE METRIC


WEATHERHEAD®
Female Swivel
30° Flare – Metric
KOMATSU, LINKBELT, ETC.



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	THREAD SIZE (MM)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-14K	1/4	M14X1.5	0.18	9/16	3/4	2.89	1 3/16
06U-18K	3/8	M18X1.5	0.31	3/4	7/8	2.86	1 7/16
08U-22K	1/2	M22X1.5	0.39	13/16	1	2.99	1 9/16
10U-24K	5/8	M24X1.5	0.49	1 1/8	1 1/4	3.64	1 11/16
12U-30K	3/4	M30X1.5	0.61	1 1/4	1 3/8	3.86	1 5/8
16U-33K	1	M33X1.5	0.81	1 3/8	1 5/8	4.53	2 5/16


British Standard
Tapered
Male Pipe (BSPT)
Rigid



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BSPT PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-154	1/4	1/4	1/4 - 19	0.16	3/4	2.51	1
06U-156	3/8	3/8	3/8 - 19	0.25	11/16	2.54	1 1/16
08U-158	1/2	1/2	1/2 - 14	0.36	7/8	2.78	1 5/16
12U-162	3/4	3/4	3/4 - 14	0.61	1 1/8	3.62	1 7/16
16U-166	1	1	1 - 11	0.81	1 3/8	4.23	2

British Standard
60° Cone BSPP
Parallel
Male Pipe Rigid




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BSPT PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-P54	1/4	1/4	1/4 - 19	0.16	11/16	2.38	7/8
06U-P56	3/8	3/8	3/8 - 19	0.25	3/4	2.48	15/16
06U-P58	3/8	1/2	1/2 - 14	0.25	1	2.62	1 1/16
08U-P56	1/2	3/8	3/8 - 19	0.33	13/16	2.54	1 1/8
08U-P58	1/2	1/2	1/2 - 14	0.36	1	2.62	1 3/16
10U-P60	5/8	5/8	5/8 - 14	0.48	1 1/8	3.25	1 5/16
12U-P62	3/4	3/4	3/4 - 14	0.61	1 1/8	3.65	1 1/2
16U-P66	1	1	1 - 11	0.81	1 3/8	3.70	1 7/16

NOTE: Retaining ring and O-Ring for port side use available


British Standard
60° Cone BSPP
Parallel
Female Pipe Swivel



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BSPT PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-354	1/4	1/4	1/4 - 19	0.16	9/16	11/16	2.58	1 1/8
06U-356	3/8	3/8	3/8 - 19	0.27	3/4	7/8	2.66	1 1/4
06U-358	3/8	1/2	1/2 - 14	0.31	7/8	1	2.73	1 5/16
08U-358	1/2	1/2	1/2 - 14	0.36	7/8	1	2.82	1 3/8
08U-360	1/2	5/8	5/8 - 14	0.36	1	1 3/16	2.96	1 9/16
12U-362	3/4	3/4	3/4 - 14	0.61	1	1 1/4	3.70	1 1/2
16U-366	1	1	1 - 11	0.81	1 1/4	1 1/2	4.40	2 3/16

British Standard
60° Cone BSPP
Parallel Female
Pipe Swivel
90° Elbow



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BSPT PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-P74	1/4	1/4	1/4 - 19	0.16	3/4	1.00	2.95	1 7/16
06U-P76	3/8	3/8	3/8 - 19	0.26	7/8	1.25	3.09	1 9/16
08U-P78	1/2	1/2	1/2 - 14	0.36	1 1/16	1.36	3.65	2 1/8
08U-P80	1/2	5/8	5/8 - 14	0.44	1 3/16	1.90	3.37	1 15/16
10U-P80	5/8	5/8	5/8 - 14	0.49	1 1/8	1.60	4.15	2 1/4
12U-P82	3/4	3/4	3/4 - 14	0.61	1 1/4	2.41	4.70	2 3/8

WEATHERHEAD HYDRAULIC


HIGH PRESSURE METRIC

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (MM)	THREAD SIZE (MM)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-08A	1/4	8	M14X1.5	0.16	9/16	2.27	1 7/16
04U-10A	1/4	10	M16X1.5	0.16	1 1/16	2.36	1 7/16
06U-12A	3/8	12	M18X1.5	0.25	3/4	2.36	1 7/16
08U-15A	1/2	15	M22X1.5	0.36	7/8	2.42	1 7/16
10U-18A	5/8	18	M26X1.5	0.48	1 1/16	2.99	1 15/16

NOTE: Retaining ring and O-Ring for port side use available


WEATHERHEAD®
Male DIN 24° Seat
Flareless – Light



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (MM)	THREAD SIZE (MM)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-06C	1/4	6	M12X1.5	0.16	9/16	1 1/16	2.23	1 7/8
04U-08C	1/4	8	M14X1.5	0.16	9/16	1 1/16	2.25	1 7/8
04U-10C	1/4	10	M16X1.5	0.16	9/16	3/4	2.45	1 7/8
06U-12C	3/8	12	M18X1.5	0.25	1 1/16	7/8	2.30	1 7/8
08U-15C	1/2	15	M22X1.5	0.36	1 3/16	1 1/16	2.46	1 7/8
10U-18C	5/8	18	M26X1.5	0.48	1 5/16	1 5/16	3.07	1 15/16
12U-22C	3/4	22	M30X2.0	0.61	1 1/8	1 7/16	3.44	2 1/8
16U-28C	1	28	M36X2.0	0.81	1 3/8	1 13/16	3.69	2 3/16
20U-35C	1 1/4	35	M45X2.0	1.02	1 11/16	2 3/16	4.44	2 5/16

Female Swivel DIN
Universal Seat
Light



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (MM)	THREAD SIZE (MM)	BORE (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-58D	1/4	8	M14X1.5	0.16	1 1/16	1.38	2.58	1 1/8
04U-60D	1/4	10	M16X1.5	0.16	3/4	1.45	2.70	1 1/4
06U-62D	3/8	12	M18X1.5	0.25	7/8	1.45	3.50	2 1/16
08U-65D	1/2	15	M22X1.5	0.36	1 1/16	1.80	3.84	2 7/16
12U-72D	3/4	22	M30X1.5	0.61	1 13/16	2.42	4.64	2 1/2

Female Swivel DIN
90° Elbow
Light

