

GATES HYDRAULIC

LOW PRESSURE - 100R4, COUPLINGS

Coupling Stems For Use Only With C4 Hose and C4 Ferrules


Ferrules For C4 Hose



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	"A" LENGTH (IN.)	"B" DIAMETER (IN.)
RB&H #	AUTOMOTIVE REFERENCE #			
12PC1F-C4	80464	3/4	1.00	1.50
16PC1F-C4	80465	1	1.125	1.75
20PC1F-C4	80466	1 1/4	1.52	2.00
24PC1F-C4	80470	1 1/2	1.56	2.25
32PC1F-C4	80472	2	2.00	2.75


NPTF Solid Male



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	BORE SIZE (IN.)	HEX SIZE (IN.)	COUPLING LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #						
12C4-12MP	80501	3/4	3/4 - 14	0.62	1 1/16	2.56	1.31
12C4-16MP	80502	3/4	1 - 11 1/2	0.62	1 3/8	2.87	1.62
16C4-16MP	80503	1	1 - 11 1/2	0.81	1 3/8	2.94	1.63
20C4-20MP	80504	1 1/4	1 1/4 - 11 1/2	1.06	1 3/4	3.54	1.72
24C4-24MP	80505	1 1/2	1 1/2 - 11 1/2	1.25	2	3.71	1.82
32C4-32MP	80506	2	2 - 11 1/2	1.69	2 1/2	4.34	1.96


NPTF Swivel Male



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	BORE SIZE (IN.)	HEX SIZE (IN.)	COUPLING LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #						
12C4-12MPX	80507	3/4	3/4 - 14	0.62	1.31	3.01	1.70
16C4-16MPX	80508	1	1 - 11 1/2	0.81	1.62	3.49	2.12

Female JIC 37° Flare Swivel




SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	BORE SIZE (IN.)	HEX SIZE (IN.)	COUPLING LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #						
12C4-12FJX	80514	3/4	1 1/16 - 12	0.62	1 1/4	2.68	1.44
12C4-14FJX	80515	3/4	1 3/16 - 12	0.62	1 3/8	2.76	1.51
12C4-16FJX	80516	3/4	1 5/16 - 12	0.62	1 1/2	2.85	1.60
16C4-16FJX	80517	1	1 5/16 - 12	0.81	1 1/2	2.90	1.59
20C4-20FJX	80518	1 1/4	1 5/8 - 12	1.06	2	3.67	1.85
24C4-24FJX	80519	1 1/2	1 7/8 - 12	1.25	2 1/4	3.98	2.09
32C4-32FJX	80521	2	2 1/2 - 12	1.69	2 7/8	4.94	2.59

O-Ring Flange Straight

CODE 61 - SAE J518



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	BORE SIZE (IN.)	NOM. FLG. SIZE (IN.)	"M" FLG. DIA. (IN.)	COUPLING LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #						
12C4-12FL	80524	3/4	0.58	3/4	1 1/2	2.98	1.73
16C4-16FL	80525	1	0.81	1	1 3/4	3.08	1.49
20C4-20FL	80526	1 1/4	1.01	1 1/4	2	3.66	1.84
24C4-24FL	80527	1 1/2	1.26	1 1/2	2 3/8	3.75	1.81
32C4-32FL	80528	2	1.69	2	2 13/16	4.44	2.06