

WEATHERHEAD HYDRAULIC**ASSORTMENT****ASSORTMENT INCLUDES**

RB&H #	QUANTITY (PCS.)	RB&H #	QUANTITY (PCS.)	RB&H #	QUANTITY (PCS.)
04U-102	5	06U-J08	5	12U-P12	5
04U-104	10	06U-P06	5	16U-116	5
04U-106	5	06U-P08	5	16U-516	2
04U-504	5	08U-058	5	16U-616	5
04U-505	5	08U-106	5	16U-676	1
04U-506	5	08U-108	10	16U-J16	1
04U-604	10	08U-112	5	41157X6	5
04U-605	5	08U-208	2	9205X2X2	5
04U-606	5	08U-508	5	9205X4X4	5
04U-664	5	08U-510	5	9205X6X6	5
04U-B04	5	08U-512	5	9205X6X8	5
04U-J04	5	08U-608	10	9205X8X6	5
06U-104	10	08U-610	5	9205X8X8	5
06U-106	10	08U-612	5	9405X4X4	5
06U-108	5	08U-668	5	9405X6X6	5
06U-206	5	08U-670	5	9405X8X8	5
06U-406	5	08U-758	5	9405X12X12	2
06U-446	5	08U-760	5	C5205X4X4	2
06U-506	5	08U-J08	5	C5205X6	4
06U-508	5	08U-P08	5	C5205X6X6	4
06U-606	10	08U-P10	5	C5205X8	4
06U-608	5	08U-R70	5	C5205X10	2
06U-610	5	12U-112	10	FH-135X	1
06U-666	5	12U-116	2	FS-1100	1
06U-668	5	12U-412	5	FS-100	1
06U-686	5	12U-512	5	FS-200	1
06U-755	5	12U-514	2	H32406	50'
06U-756	5	12U-516	2	H42504	50'
06U-B05	5	12U-610	5	H42506	50'
06U-B06	5	12U-612	10	H42508	50'
06U-B46	5	12U-614	5	H42512	50'
06U-B66	5	12U-616	2	H42516	50'
06U-J04	5	12U-672	2	T-401	1
06U-J06	5	12U-J12	5	-	-

WEATHERHEAD®
Coll-O-Crimp®
I Assortment



This assortment includes everything you need to start servicing hydraulic hose applications in your own shop. Five sizes of 2 wire hose along with a variety of hose ends and adapters gives you the versatility you need. In addition there is hose for power steering applications and a cabinet for storage.

Other assortments available that include:

- Cut off Saw
- Saw Table
- Hose Crimper
- Reel Racks
- Labels


WEATHERHEAD HYDRAULIC

HIGH PRESSURE

WEATHERHEAD®

Weatherhead Coll-O-Crimp "U" Series Fittings for H425, H245, H104, H145, and H324 Hose


Male Pipe Rigid



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-102	1/4	1/8	1/8 - 27	0.16	9/16	2.31	7/8
04U-104	1/4	1/4	1/4 - 18	0.16	9/16	2.49	15/16
04U-106	1/4	3/8	3/8 - 18	0.16	11/16	2.52	1 1/8
04U-108	1/4	1/2	1/2 - 14	0.16	7/8	2.77	1 11/16
06U-104	3/8	1/4	1/4 - 18	0.25	11/16	2.52	1 1/8
06U-106	3/8	3/8	3/8 - 18	0.25	1 11/16	2.52	1 1/8
06U-108	3/8	1/2	1/2 - 14	0.25	7/8	2.77	1 3/8
08U-104	1/2	1/4	1/4 - 18	0.28	13/16	2.56	1 13/16
08U-106	1/2	3/8	3/8 - 18	0.36	3/4	2.57	1 3/16
08U-108	1/2	1/2	1/2 - 14	0.36	7/8	2.75	1 5/16
08U-112	1/2	3/4	3/4 - 14	0.36	1 1/16	2.83	1 3/8
10U-106	5/8	3/8	3/8 - 18	0.41	15/16	3.12	1 1/4
10U-108	5/8	1/2	1/2 - 14	0.49	15/16	3.31	1 7/16
10U-112	5/8	3/4	3/4 - 14	0.49	1 1/16	3.31	1 3/8
12U-108	3/4	1/2	1/2 - 14	0.53	1	3.62	1 7/16
12U-112	3/4	3/4	3/4 - 14	0.61	1 1/16	3.61	1 7/16
12U-116	3/4	1	1 - 11 1/2	0.61	1 3/8	3.84	1 11/16
16U-112	1	3/4	3/4 - 14	0.81	1 1/4	4.23	1 3/4
16U-116	1	1	1 - 11 1/2	0.81	1 3/8	3.90	1 11/16
20U-120	1 1/4	1 1/4	1 1/4 - 11 1/2	1.02	1 11/16	4.61	2 5/16


Male Pipe Swivel



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-J04	1/4	1/4	1/4 - 18	0.16	5/8	13/16	3.38	1 7/8
06U-J04	3/8	1/4	1/4 - 18	0.25	11/16	13/16	3.40	1 15/16
06U-J06	3/8	3/8	3/8 - 18	0.25	11/16	7/8	3.38	1 15/16
06U-J08	3/8	1/2	1/2 - 14	0.25	3/4	7/8	3.60	2 3/16
08U-J08	1/2	1/2	1/2 - 14	0.35	13/16	7/8	3.60	2 3/16
12U-J12	3/4	3/4	3/4 - 14	0.61	1	1 1/4	4.73	2 9/16
16U-J16	1	1	1 - 11 1/2	0.80	1 1/4	1 3/8	5.06	2 7/8

Male Pipe Swivel 90° Elbow



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" NUT HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-M04	1/4	1/4	1/4 - 18	0.15	11/16	13/16	1.79	2.43	1
06U-M04	3/8	1/4	1/4 - 18	0.24	11/16	13/16	1.83	2.50	1 1/16
06U-M06	3/4	3/8	3/8 - 18	0.24	11/16	7/8	1.84	2.50	1 1/16
08U-M08	1/2	1/2	1/2 - 14	0.35	3/4	7/8	1.96	2.75	1 5/16


WEATHERHEAD HYDRAULIC

HIGH PRESSURE

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-202	1/4	1/8	1/8 - 27	0.16	5/8	2.20	1 1/2
04U-204	1/4	1/4	1/4 - 18	0.16	3/4	2.43	1 1/2
06U-204	3/8	1/4	1/4 - 18	0.25	3/4	2.46	1 7/16
06U-206	3/8	3/8	3/8 - 18	0.25	7/8	2.57	1 7/16
08U-208	1/2	1/2	1/2 - 14	0.36	1 1/8	2.82	1 7/16
12U-212	3/4	3/4	3/4 - 14	0.61	1 3/8	3.71	2 1/8


**WEATHERHEAD®
Female Pipe Rigid**



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-254	1/4	1/4	1/4 - 18	0.16	5/8	13/16	3.52	2 1/16
06U-256	3/8	3/8	3/8 - 18	0.25	1 1/16	7/8	3.61	2 3/16
08U-258	1/2	1/2	1/2 - 14	0.36	1 3/16	1 1/8	3.85	2 7/16
12U-262	3/4	3/4	3/4 - 14	0.61	1	1 3/8	4.81	2 5/8


Female Pipe Swivel



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	PIPE SIZE (IN.)	NPSM THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-054	1/4	1/4	1/4 - 18	0.16	1/2	1 1/16	2.55	1 1/8
06U-056	3/8	3/8	3/8 - 18	0.25	1 1/16	7/8	2.65	1 1/4
08U-058	1/2	1/2	1/2 - 14	0.36	1 3/16	1	2.85	1 7/16
12U-062	3/4	3/4	3/4 - 14	0.61	1	1 1/4	3.77	1 5/8
16U-066	1	1	1 - 11 1/2	0.81	1 3/8	1 1/2	4.34	2 1/8
20U-070	1 1/4	1 1/4	1 1/4 - 11 1/2	1.02	1 1 1/16	1 7/8	4.76	2 7/16

Female Straight Pipe Swivel




NOTE: Connects to male pipe fitting with internal seat

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-504	1/4	1/4	7/16 - 20	0.16	1/2	2.48	1
04U-505	1/4	5/16	1/2 - 20	0.16	9/16	2.51	1
04U-506	1/4	3/8	9/16 - 18	0.16	5/8	2.55	1
06U-506	3/8	3/8	9/16 - 18	0.25	1 1/16	2.54	1
06U-508	3/8	1/2	3/4 - 16	0.25	1 3/16	2.67	1 1/4
06U-510	3/8	5/8	7/8 - 14	0.25	1 15/16	2.83	1 5/16
08U-508	1/2	1/2	3/4 - 16	0.38	1 3/16	2.70	1 3/16
08U-510	1/2	5/8	7/8 - 14	0.36	1 5/16	2.83	1 5/16
08U-512	1/2	3/4	1 1/16 - 12	0.36	1 1/8	2.87	1 7/16
10U-508	5/8	1/2	3/4 - 16	0.39	1 5/16	3.22	1 5/16
10U-510	5/8	5/8	7/8 - 14	0.48	1 5/16	3.32	1 3/8
10U-512	5/8	3/4	1 1/16 - 12	0.48	1 1/8	3.42	1 7/16
12U-510	3/4	5/8	7/8 - 14	0.42	1	3.64	1 7/16
12U-512	3/4	3/4	1 1/16 - 12	0.61	1 1/8	3.74	1 9/16
12U-514	3/4	7/8	1 3/16 - 12	0.67	1 1/4	3.81	1 5/8
12U-516	3/4	1	1 5/16 - 12	0.83	1 3/8	3.81	1 5/8
16U-514	1	7/8	1 3/16 - 12	0.67	1 3/8	4.18	1 15/16
16U-516	1	1	1 5/16 - 12	0.83	1 3/8	4.20	2
16U-520	1	1 1/4	1 5/8 - 12	0.81	1 1 1/16	4.02	1 13/16
20U-520	1 1/4	1 1/4	1 5/8 - 12	1.06	1 1 1/16	4.60	2 5/16


**SAE 37° JIC
Male Rigid**



WEATHERHEAD HYDRAULIC

HIGH PRESSURE


WEATHERHEAD®
SAE 37° JIC
Male Rigid
90° Elbow



SPECIFICATIONS

RB&H #	HOSE L.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-X60	3/8	5/8	7/8 - 14	0.25	1 1/16	1.10	2.50	1 1/16
08U-X60	1/2	5/8	7/8 - 14	0.36	3/4	1.13	2.75	1 5/16
12U-X60	3/4	5/8	7/8 - 14	0.48	1 1/8	1.32	3.40	1 1/4


SAE 45° Flare
Male Rigid



SPECIFICATIONS

RB&H #	HOSE L.D. (IN.)	MALE PIPE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-306	3/8	3/8	5/8 - 18	0.25	1 1/16	2.60	1 1/8
12U-312	3/4	3/4	1 1/16 - 14	0.61	1 1/8	3.87	1 11/16

SAE 37° JIC
Female Swivel
 EXCEPTIONS NOTED



SPECIFICATIONS

RB&H #	HOSE L.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-604 ^a	1/4	1/4	7/16 - 20	0.16	9/16	9/16	2.61	1 3/16
04U-605 ^a	1/4	5/16	1/2 - 20	0.16	9/16	5/8	2.67	1 1/4
04U-606 ^c	1/4	3/8	9/16 - 18	0.16	9/16	1 1/16	2.68	1 1/4
06U-604 ^a	3/8	1/4	7/16 - 20	0.17	1 1/16	9/16	2.66	1 1/4
06U-406 ^b	3/8	3/8	5/8 - 18	0.25	1 1/16	3/4	2.68	1 1/4
06U-606 ^c	3/8	3/8	9/16 - 18	0.25	1 1/16	1 1/16	2.71	1 5/16
06U-608 ^a	3/8	1/2	3/4 - 16	0.25	3/4	7/8	2.86	1 7/16
06U-610 ^a	3/8	5/8	7/8 - 14	0.25	7/8	1	3.00	1 5/8
06U-612 ^c	3/8	3/4	1 1/16 - 12	0.25	1	1 1/4	3.15	1 3/4
08U-608 ^a	1/2	1/2	3/4 - 16	0.36	1 3/16	7/8	2.79	1 3/8
08U-610 ^a	1/2	5/8	7/8 - 14	0.36	7/8	1	3.00	1 9/16
08U-612 ^c	1/2	3/4	1 1/16 - 12	0.36	1 1/16	1 1/4	3.12	1 7/16
08U-616 ^c	1/2	1	1 5/16 - 12	0.36	1 1/4	1 1/2	3.17	1 3/4
10U-608 ^a	5/8	1/2	3/4 - 16	0.39	1 5/16	7/8	3.48	1 9/16
10U-610 ^a	5/8	5/8	7/8 - 14	0.49	1 5/16	1	3.53	1 5/8
10U-612 ^c	5/8	3/4	1 1/16 - 12	0.49	1 1/8	1 1/4	3.64	1 3/4
12U-610 ^a	3/4	5/8	7/8 - 14	0.48	1	1	3.75	1 9/16
12U-412 ^b	3/4	3/4	1 1/16 - 14	0.61	1	1 1/4	3.86	1 11/16
12U-612 ^c	3/4	3/4	1 1/16 - 12	0.61	1	1 1/4	3.86	1 11/16
12U-614 ^c	3/4	7/8	1 3/16 - 12	0.61	1 1/4	1 3/8	3.88	1 11/16
12U-616 ^c	3/4	1	1 5/16 - 12	0.61	1 1/4	1 1/2	4.07	1 7/8
16U-614 ^c	1	7/8	1 3/16 - 12	0.72	1 3/8	1 3/8	4.35	2 1/8
16U-616 ^c	1	1	1 5/16 - 12	0.81	1 3/8	1 1/2	4.46	2 1/4
16U-620 ^c	1	1 1/4	1 5/8 - 12	0.81	1 5/8	2	4.30	2 3/16
20U-620 ^c	1 1/4	1 1/4	1 5/8 - 12	1.02	1 11/16	2	4.90	2 9/16

Exceptions

- a - Swivel nuts are universal. Both SAE 45° and JIC 37° connections
- b - SAE 45° connection only
- c - JIC 37° connection only


WEATHERHEAD HYDRAULIC

HIGH PRESSURE

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-684 ^a	¼	¼	7/16 - 20	0.15	9/16	9/16	0.33	3.05	1 9/16
04U-685 ^a	¼	5/16	½ - 20	0.16	9/16	5/8	0.36	3.14	1 11/16
06U-684 ^a	3/8	¼	7/16 - 20	0.15	1 1/16	9/16	0.33	3.08	1 11/16
06U-486 ^c	3/8	3/8	5/8 - 18	0.24	1 1/16	13/16	0.39	3.18	1 3/4
06U-686 ^c	3/8	3/8	9/16 - 18	0.24	1 1/16	1 1/16	0.39	3.17	1 3/4
06U-688 ^a	3/8	½	¾ - 16	0.33	¾	7/8	0.55	3.46	2
08U-688 ^a	½	½	¾ - 16	0.33	13/16	7/8	0.55	3.44	2
08U-690 ^a	½	5/8	7/8 - 14	0.46	13/16	1	0.63	3.57	2 3/16
10U-692 ^c	5/8	¾	1 1/16 - 12	0.48	-	1 ¼	0.78	4.43	2 ½
12U-692 ^c	¾	¾	1 1/16 - 12	0.48	1	1 ¼	0.78	4.74	2 9/16
16U-696 ^c	1	1	1 5/16 - 12	0.74	1 ½	1 ½	0.89	5.00	3 7/16


WEATHERHEAD®
SAE (37°) JIC
Female Swivel
45° Tube Elbow
 EXCEPTIONS NOTED



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-664 ^a	¼	¼	7/16 - 20	0.15	9/16	9/16	0.68	2.87	1 9/16
04U-665 ^a	¼	5/16	½ - 20	0.21	9/16	5/8	0.77	3.19	1 ¾
04U-666 ^c	¼	3/8	9/16 - 18	0.25	9/16	1 1/16	0.85	3.08	1 9/16
06U-664 ^a	3/8	¼	7/16 - 20	0.15	1 1/16	9/16	0.68	2.85	1 7/16
06U-666 ^c	3/8	3/8	9/16 - 18	0.24	1 1/16	1 1/16	0.85	3.07	1 5/8
06U-668 ^a	3/8	½	¾ - 16	0.33	¾	7/8	1.09	3.27	1 ¾
08U-668 ^a	½	½	¾ - 16	0.33	13/16	7/8	1.09	3.25	1 ¾
08U-670 ^a	½	5/8	7/8 - 14	0.46	13/16	1	1.23	3.79	2 5/16
10U-670 ^a	5/8	5/8	7/8 - 14	0.46	13/16	1	1.23	4.25	2 ¼
10U-672 ^c	5/8	¾	1 1/16 - 14	0.48	-	1 ¼	1.82	5.05	3 1/8
12U-670 ^a	¾	5/8	7/8 - 14	0.46	1	1	1.23	4.34	2 3/16
12U-672 ^c	¾	¾	1 1/16 - 12	0.58	1	1 ¼	1.82	4.69	2 ½
16U-676 ^c	1	1	1 5/16 - 12	0.83	1 3/8	1 ½	2.14	5.18	2 15/16
20U-677 ^c	1 ¼	1 ¼	1 5/8 - 12	1.01	1 5/8	2	3.31	5.31	3


SAE 37° JIC
Female Swivel
90° Tube Elbow
 EXCEPTIONS NOTED



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-644 ^a	3/8	¼	7/16 - 20	0.15	1 1/16	9/16	1.80	2.89	1 ½
06U-446 ^b	3/8	3/8	5/8 - 18	0.24	1 1/16	¾	2.18	3.07	1 5/8
06U-646 ^c	3/8	3/8	9/16 - 18	0.24	1 1/16	1 1/16	2.18	3.07	1 5/8
08U-648 ^a	½	½	¾ - 16	0.33	13/16	7/8	2.43	3.33	1 11/16
08U-650 ^a	½	5/8	7/8 - 14	0.36	13/16	1	2.57	3.58	2 3/16
12U-652 ^a	¾	¾	1 1/16 - 12	0.58	1	1 ¼	3.73	4.69	2 ½
16U-656L33 ^c	1	1	1 5/16 - 12	0.76	-	1 ½	3.37	5.18	3

SAE 37° JIC
Female Swivel
Long Drop
90° Tube Elbow
 EXCEPTIONS NOTED



Exceptions


- a - Swivel nuts are universal. Both SAE 45° and JIC 37° connections
- b - SAE 45° connection only
- c - JIC 37° connection only

WEATHERHEAD HYDRAULIC

HIGH PRESSURE

**WEATHERHEAD®
SAE 37° JIC
Female Swivel
(90° Elbow)**

EXCEPTIONS NOTED




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" SQUARE (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-554°	¼	¼	7/16 - 20	0.16	1 1/16	9/16	1.03	2.43	1
06U-556°	3/8	3/8	9/16 - 18	0.25	1 1/16	1 1/16	1.15	2.50	1 1/16
08U-558°	½	½	¾ - 16	0.36	1 1/16	7/8	1.29	2.75	1 5/16
08U-560°	½	5/8	7/8 - 14	0.36	1 3/16	1	1.34	2.75	1 5/16
12U-560°	¾	5/8	7/8 - 14	0.61	1 3/16	1	1.54	4.15	2

Exceptions

c - JIC 37° flare connection only

**Male Straight Thread
O-Ring Rigid**




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-P04	¼	¼	7/16 - 20	0.16	9/16	2.29	1 3/16
04U-P05	¼	5/16	½ - 20	0.16	5/8	2.32	7/8
04U-P06	¼	3/8	9/16 - 18	0.16	1 1/16	2.35	7/8
06U-P06	3/8	3/8	9/16 - 18	0.25	1 1/16	2.35	1 5/16
06U-P08	3/8	½	¾ - 16	0.25	7/8	2.46	1 1/16
06U-P10	3/8	5/8	7/8 - 14	0.25	1	2.57	1 1/8
08U-P08	½	½	¾ - 16	0.36	7/8	2.46	1 1/16
08U-P10	½	5/8	7/8 - 14	0.36	1	2.55	1 1/8
08U-P12	½	¾	1 1/16 - 12	0.36	1 ¼	2.66	1 ¼
10U-P08	5/8	½	¾ - 16	0.48	1 5/16	3.00	1 1/8
10U-P10	5/8	5/8	7/8 - 14	0.48	1	3.06	1 3/16
10U-P12	5/8	¾	1 1/16 - 12	0.49	1 ¼	3.15	1 ¼
12U-P10	¾	5/8	7/8 - 14	0.49	1	3.36	1 3/16
12U-P12	¾	¾	1 1/16 - 12	0.61	1 ¼	3.49	1 5/16
12U-P16	¾	1	1 5/16 - 12	0.61	1 ½	3.50	1 5/16
16U-P16	1	1	1 5/16 - 12	0.81	1 ½	3.63	1 7/16
20U-P20	1 ¼	1 ¼	1 5/8 - 12	1.02	1 7/8	4.23	1 15/16

Includes O-Ring

**Male Straight Thread
O-Ring Swivel**



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-R06	3/8	3/8	9/16 - 18	0.25	1 1/16	7/8	3.25	1 13/16
06U-R08	3/8	½	¾ - 16	0.25	1 1/16	7/8	3.25	1 13/16
08U-R08	½	½	¾ - 16	0.36	1 3/16	7/8	3.27	1 13/16
08U-R10	½	5/8	7/8 - 14	0.36	1 3/16	1 1/8	3.41	1 15/16
08U-R12	½	¾	1 1/16 - 12	0.36	1 3/16	1 ¼	3.57	2 1/16
10U-R08	5/8	½	¾ - 16	0.42	1 5/16	1 1/8	3.85	2
12U-R10	¾	5/8	7/8 - 14	0.49	1	1 1/8	4.23	2 1/16

Includes O-ring

WEATHERHEAD HYDRAULIC


HIGH PRESSURE

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-R66	1/4	3/8	9/16 - 18	0.16	1 1/16	7/8	1.62	2.45	7/8
06U-R66	3/8	3/8	9/16 - 18	0.25	1 1/16	7/8	1.64	2.53	1 1/16
06U-R68	3/8	1/2	3/4 - 16	0.25	1 1/16	7/8	1.64	2.50	1 1/16
06U-R70	3/8	5/8	7/8 - 14	0.25	1 1/16	1	1.80	2.50	1 1/16
08U-R68	1/2	1/2	3/4 - 16	0.36	3/4	7/8	1.64	2.75	1 3/8
08U-R70	1/2	5/8	7/8 - 14	0.36	3/4	1 1/8	1.79	2.75	1 3/8
08U-R72	1/2	3/4	1 1/16 - 12	0.36	3/4	1 1/4	1.89	2.75	1 1/4
12U-R72	3/4	3/4	1 1/16 - 12	0.61	1 1/8	1 7/16	2.24	4.15	2

Includes O-Ring


WEATHERHEAD®
Male Straight Thread
O-Ring Swivel
90° Elbow



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-B03	1/4	3/16	3/8 - 24	0.12	9/16	3/8	3.75
04U-B04	1/4	1/4	7/16 - 24	0.16	9/16	7/16	3.14
04U-B05	1/4	5/16	1/2 - 20	0.16	9/16	1/2	3.13
06U-B04	3/8	1/4	7/16 - 24	0.16	1 1/16	7/16	3.12
06U-B05	3/8	5/16	1/2 - 20	0.21	1 1/16	1/2	3.16
06U-B06	3/8	1/2	5/8 - 18	0.26	1 1/16	5/8	3.31
06U-B07	3/8	7/16	1 1/16 - 18	0.24	1 1/16	1 1/16	3.31
08U-B08	1/2	1/2	3/4 - 18	0.36	1 3/16	3/4	3.69
08U-B10	1/2	5/8	7/8 - 18	0.36	1 3/16	7/8	3.43


Inverted Male Swivel
Straight



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-B43	1/4	3/16	3/8 - 24	0.12	9/16	3/8	0.69	3.48	2
04U-B44	1/4	1/4	7/16 - 24	0.15	9/16	7/16	0.93	3.61	2 1/8
04U-B45	1/4	5/16	1/2 - 20	0.21	9/16	1/2	1.14	3.98	2 1/2
06U-B44	3/8	1/4	7/16 - 24	0.15	1 1/16	7/16	0.93	3.59	2 3/16
06U-B45	3/8	5/16	1/2 - 20	0.21	1 1/16	1/2	1.14	4.02	2 9/16
06U-B46	3/8	3/8	5/8 - 18	0.24	1 1/16	5/8	1.34	4.05	2 5/8
06U-B47	3/8	7/16	1 1/16 - 18	0.24	1 1/16	1 1/16	1.34	4.05	2 5/8
08U-B48	1/2	1/2	3/4 - 18	0.33	1 3/16	3/4	1.58	4.85	3 7/16


Inverted Male Swivel
45° Tube Elbow



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-B63	1/4	3/16	3/8 - 24	0.12	9/16	3/8	1.06	2.85	1 3/8
04U-B64	1/4	1/4	7/16 - 24	0.15	9/16	7/16	1.36	2.82	1 5/16
04U-B65	1/4	5/16	1/2 - 20	0.21	9/16	1/2	1.61	3.01	1 1/2
06U-B64	3/8	1/4	7/16 - 24	0.15	1 1/16	7/16	1.36	2.84	1 5/16
06U-B65	3/8	5/16	1/2 - 20	0.21	1 1/16	1/2	1.61	3.05	1 1/2
06U-B66	3/8	3/8	5/8 - 18	0.24	1 1/16	5/8	1.97	3.28	1 7/8
06U-B67	3/8	7/16	1 1/16 - 18	0.24	1 1/16	1 1/16	1.97	3.40	2 1/16
08U-B68	1/2	1/2	3/4 - 18	0.35	1 3/16	3/4	2.32	3.50	2 1/16


Inverted Male Swivel
90° Tube Elbow



WEATHERHEAD HYDRAULIC

HIGH PRESSURE

**WEATHERHEAD®
FOR-SEAL®
Male Rigid**




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-E64	1/4	1/4	9/16 - 18	0.17	5/8	2.34	1 13/16
06U-E66	3/8	3/8	1 1/16 - 16	0.26	3/4	2.43	1
08U-E68	1/2	1/2	1 3/16 - 16	0.38	7/8	2.54	1 1/16
10U-E70	5/8	5/8	1 - 14	0.48	1 1/16	3.20	1 1/4
12U-E72	3/4	3/4	1 3/16 - 12	0.61	1 1/4	3.58	1 7/16
12U-E76	3/4	1	1 7/16 - 12	0.61	1 1/2	3.60	1 7/16
16U-E76	1	1	1 7/16 - 12	0.81	1 1/2	3.73	1 1/2
20U-E80	1 1/4	1 1/4	1 11/16 - 12	1.02	1 3/4	4.10	1 13/16

Does not include O-Ring


**Female FOR-SEAL®
Swivel (Straight)**



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-S64	1/4	1/4	9/16 - 18	0.16	9/16	1 1/16	2.82	1 5/16
04U-S66	1/4	3/8	1 1/16 - 16	0.26	9/16	1 3/16	2.85	1 3/8
04U-S68	1/4	1/2	1 3/16 - 16	0.36	1 1/16	1 5/16	3.19	1 3/4
06U-S66	3/8	3/8	1 1/16 - 16	0.26	1 1/16	1 3/16	2.87	1 1/2
06U-S68	3/8	1/2	1 3/16 - 16	0.28	1 1/16	1 5/16	3.22	1 3/4
08U-S68	1/2	1/2	1 3/16 - 16	0.36	1 3/16	1 5/16	3.15	1 3/4
08U-S70	1/2	5/8	1 - 14	0.47	1 3/16	1 7/8	3.30	1 7/8
08U-S72	1/2	3/4	1 3/16 - 12	0.36	1	1 3/8	3.28	1 7/8
10U-S70	5/8	5/8	1 - 14	0.46	1 5/16	1 7/8	3.76	1 7/8
10U-S72	5/8	3/4	1 3/16 - 12	0.55	1	1 3/8	3.70	1 3/4
12U-S72	3/4	3/4	1 3/16 - 12	0.55	1	1 3/8	4.06	1 7/8
12U-S76	3/4	1	1 7/16 - 12	0.81	1 1/8	1 5/8	4.19	1 15/16
16U-S72	1	3/4	1 3/16 - 12	0.55	1 3/4	1 3/8	4.06	1 13/16
16U-S76	1	1	1 7/16 - 12	0.76	1 1/4	1 5/8	4.43	2 7/32
20U-S80	1 1/4	1 1/4	1 11/16 - 12	1.04	1 11/16	1 7/8	4.54	2 1/4

**Female FOR-SEAL®
Swivel
45° Tube Elbow**



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-L64	1/4	1/4	9/16 - 18	0.16	9/16	1 1/16	0.37	3.09	1 5/8
04U-L66	1/4	3/8	1 1/16 - 16	0.16	9/16	1 3/16	0.48	3.28	1 3/4
06U-L66	3/8	3/8	1 3/16 - 16	0.26	1 1/16	1 3/16	0.48	3.25	1 3/4
06U-L68	3/8	1/2	1 1/16 - 16	0.26	1 1/16	1 5/16	0.60	3.58	2 1/8
08U-L68	1/2	1/2	1 3/16 - 16	0.36	1 3/16	1 5/16	0.60	3.56	2 1/8
08U-L70	1/2	5/8	1 3/16 - 16	0.36	-	1 1/16	0.68	3.68	2 1/4
10U-L70	5/8	5/8	1 - 14	0.46	1 5/16	1 7/8	0.68	4.07	2 3/16
10U-L72	5/8	3/4	1 3/16 - 12	0.48	-	1 3/8	0.84	4.57	2 9/16
12U-L70	3/4	5/8	1 - 14	0.46	-	1 1/16	0.68	4.48	2 5/16
12U-L72	3/4	3/4	1 3/16 - 12	0.59	1 1/8	1 3/8	0.84	4.96	2 13/16
16U-L76	1	1	1 7/16 - 12	0.76	1 1/4	1 5/8	0.95	5.29	3 3/32
20U-L80	1 1/4	1 1/4	1 11/16 - 12	1.04	-	2 1/4	1.00	5.00	3 11/16


WEATHERHEAD HYDRAULIC

HIGH PRESSURE

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-A24	1/4	1/4	9/16 - 18	0.16	9/16	5/8	0.78	3.10	1 5/8
04U-A26	1/4	3/8	1 1/16 - 16	0.16	9/16	13/16	0.90	3.08	1 5/8
06U-A24	3/8	1/4	9/16 - 18	0.16	1 1/16	5/8	0.78	3.10	1 5/8
06U-A26	3/8	3/8	1 1/16 - 16	0.26	1 1/16	13/16	0.90	3.11	1 11/16
06U-A28	3/8	1/2	13/16 - 16	0.26	1 1/16	15/16	1.15	3.24	1 13/16
08U-A26	1/2	3/8	1 1/16 - 16	0.26	13/16	13/16	0.90	3.25	1 13/16
08U-A28	1/2	1/2	13/16 - 16	0.36	13/16	15/16	1.15	3.34	1 7/8
08U-A30	1/2	3/4	1 3/16 - 16	0.36	-	1 3/8	1.88	3.98	2 9/16
10U-A30	5/8	5/8	1 - 14	0.46	15/16	1 1/8	1.27	3.83	1 19/16
10U-A32	5/8	3/4	1 3/16 - 12	0.46	1	1 3/8	1.88	4.33	2 7/16
12U-A30	3/4	5/8	1 - 14	0.46	-	1 1/8	1.27	4.26	2 1/8
12U-A32	3/4	3/4	1 3/16 - 12	0.55	1	1 3/8	1.88	4.69	2 7/16
12U-A36	3/4	1	1 7/16 - 12	0.61	-	1 5/8	2.21	5.13	3
16U-A36	1	1	1 7/16 - 12	0.76	1 1/4	1 5/8	2.21	5.23	3 1/32
16U-A40	1	1 1/4	1 11/16 - 12	1.02	-	1 7/8	2.51	5.24	3
20U-A40	1 1/4	1 1/4	1 11/16 - 12	1.02	1 5/8	1 7/8	2.51	5.10	3


WEATHERHEAD®
Female FOR-SEAL®
Swivel (Short Drop)
(90° Tube Elbow)



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-J34	1/4	1/4	9/16 - 18	0.16	9/16	1 1/16	1.26	2.94	1 7/16
04U-J36	1/4	3/8	1 1/16 - 16	0.16	9/16	13/16	1.51	3.13	1 1/2
04U-J38	1/4	1/2	13/16 - 16	0.16	1 1/16	15/16	1.62	3.25	1 3/4
06U-J36	3/8	3/8	1 1/16 - 18	0.26	1 1/16	13/16	1.51	3.06	1 5/8
06U-J38	3/8	1/2	13/16 - 16	0.26	1 1/16	15/16	1.62	3.24	1 3/4
08U-J36	1/2	3/8	1 1/16 - 16	0.26	13/16	13/16	1.51	3.12	1 11/16
08U-J38	1/2	1/2	13/16 - 16	0.36	13/16	15/16	1.62	3.24	1 3/4
08U-J42	1/2	3/4	1 3/16 - 12	0.36	1	1 3/8	2.28	3.88	2 7/16
12U-J40	3/4	5/8	1 - 14	0.46	1	1 1/4	1.85	4.29	2 1/8
12U-J42	3/4	3/4	1 3/16 - 12	0.58	-	1 5/8	2.28	4.73	2 9/16
16U-J46	1	1	1 7/16 - 12	0.76	1 1/4	1 5/8	2.78	5.44	3 1/4
16U-J50	1	1 1/4	1 11/16 - 12	0.76	1 1/2	1 7/8	3.01	5.24	3 1/32


Female FOR-SEAL®
Swivel
(Medium Drop)
(90° Tube Elbow)



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" DIAMETER (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-A64	1/4	1/4	9/16 - 18	0.16	9/16	1 1/16	1.80	3.14	1 11/16
04U-A66	1/4	3/8	1 1/16 - 16	0.16	-	13/16	2.13	3.31	1 13/16
06U-A66	3/8	3/8	1 1/16 - 16	0.26	1 1/16	13/16	2.13	3.34	1 7/8
06U-A68	3/8	1/2	13/16 - 16	0.26	-	15/16	2.51	3.37	1 15/16
08U-A68	1/2	1/2	13/16 - 16	0.36	13/16	15/16	2.51	3.37	1 15/16
08U-A70	1/2	5/8	1 - 14	0.36	-	15/16	2.76	3.46	2 1/16
10U-A70	5/8	5/8	1 - 14	0.46	15/16	1 1/8	2.76	3.93	2
12U-A72	3/4	3/4	1 3/16 - 12	0.55	1	1 3/8	3.78	4.72	2 1/2
16U-A76	1	1	1 7/16 - 12	0.78	1 3/8	1 5/8	4.50	5.18	2 15/16
20U-A80	1 1/4	1 1/4	1 3/16 - 12	1.04	1 5/8	1 7/8	5.09	5.29	3

Female FOR-SEAL®
Swivel
(Long Drop)
(90° Tube Elbow)




WEATHERHEAD HYDRAULIC

HIGH PRESSURE

**WEATHERHEAD®
Split Flange
(Straight)**

CODE 61




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BORE (IN.)	NOMINAL FLANGE SIZE (IN.)	"G" FLANGE DIA. (IN.)	"T" FLANGE WIDTH (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
08U-G08	1/2	0.33	1/2	1.19	.265	3.87	2 5/16
12U-G12	3/4	0.58	3/4	1.50	.265	4.38	2 3/16
12U-G16	3/4	0.58	1	1.75	.315	4.38	2 3/16
16U-G16	1	0.77	1	1.75	.315	4.58	2 3/8
16U-G20	1	0.77	1 1/4	2.00	.315	4.58	2 3/8
20U-G20	1 1/4	1.02	1 1/4	2.00	.315	5.04	2 3/4
20U-G24	1 1/4	1.02	1 1/2	2.38	.315	5.10	2 13/16

Flange halves, kits and O-Rings available

**Split Flange
(Straight)**

KOMATSU, LINKBELT, ETC.




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BORE (IN.)	NOMINAL FLANGE SIZE (IN.)	"G" FLANGE DIA. (IN.)	"T" FLANGE WIDTH (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
10U-K09	5/8	0.46	5/8	1.335	.265	4.09	2 3/16

**Split Flange
45° Tube Elbow**

CODE 61




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BORE (IN.)	NOMINAL FLANGE SIZE (IN.)	"G" FLANGE DIA. (IN.)	"T" FLANGE WIDTH (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
08U-G41	1/2	0.41	1/2	1.19	.265	0.78	3.68	2 1/4
12U-G42	3/4	0.58	3/4	1.50	.265	1.00	4.82	2 5/8
12U-G46	3/4	0.58	1	1.75	.315	1.00	4.82	2 5/8
16U-G46	1	0.77	1	1.75	.315	1.06	5.00	3 3/16
16U-G50	1	0.77	1 1/4	2.00	.315	1.06	5.00	3 3/16
20U-G50	1 1/4	1.02	1 1/4	2.00	.315	1.15	5.13	2 7/8

Flange halves, kits and O-Rings available

**Split Flange
(45° tube elbow)**

KOMATSU, LINKBELT, ETC.




SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BORE (IN.)	NOMINAL FLANGE SIZE (IN.)	"G" FLANGE DIA. (IN.)	"T" FLANGE WIDTH (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
10U-K69	5/8	0.46	5/8	1.335	.265	0.94	4.21	2 5/16

**Split Flange
90° Tube Elbow**

CODE 61



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	BORE (IN.)	NOMINAL FLANGE SIZE (IN.)	"G" FLANGE DIA. (IN.)	"T" FLANGE WIDTH (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
08U-G71	1/2	0.41	1/2	1.19	.265	1.63	3.53	1 15/16
12U-G72	3/4	0.58	3/4	1.50	.265	2.13	4.65	2 1/2
12U-G76	3/4	0.58	1	1.75	.315	2.13	4.65	2 1/2
16U-G76	1	0.77	1	1.75	.315	2.38	5.18	3
16U-G80	1	0.77	1 1/4	2.00	.315	2.38	5.18	3

Flange halves, kits and O-Rings available


WEATHERHEAD HYDRAULIC

HIGH PRESSURE

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-754	1/4	1/4	7/16 - 20	0.16	9/16	9/16	2.38	1 15/16
04U-755	1/4	5/16	1/2 - 20	0.16	11/16	5/8	2.42	1
06U-754	3/8	1/4	7/16 - 20	0.20	11/16	9/16	2.43	1
06U-755	3/8	5/16	1/2 - 20	0.23	11/16	5/8	2.40	1
06U-756	3/8	3/8	9/16 - 18	0.25	11/16	11/16	2.42	1
08U-758	1/2	1/2	3/4 - 16	0.36	3/4	7/8	2.51	1 1/8
08U-760	1/2	5/8	7/8 - 14	0.36	7/8	1	2.64	1 1/4
12U-762	3/4	3/4	1 1/16 - 12	0.61	1 1/8	1 1/4	3.55	1 5/16
16U-766	1	1	1 5/16 - 12	0.81	1 3/8	1 1/2	3.98	1 3/4
20U-770	1 1/4	1 1/4	1 5/8 - 12	1.02	1 5/8	2	4.35	2


WEATHERHEAD®
Flareless Tube Rigid
(WITH NUT AND SLEEVE)



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-C34	1/4	.511 - 27	0.16	3/4	2.45	1
06U-C36	3/8	.511 - 27	0.25	3/4	2.44	1


Female Grease Tap



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	"E" DIAMETER (IN.)	"F" DIAMETER (MM)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-L06	3/8	7/8	0.62	2.64	1 1/16


Banjo
FORD TRACTOR



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE O.D. (IN.)	BORE (IN.)	"F" STEM HEX SIZE (IN.)	"B" DROP (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
04U-T04	1/4	1/4	0.15	9/16	1.10	3.16	1 11/16
06U-T06	3/8	3/8	0.25	11/16	1.30	3.36	1 15/16
08U-T08	1/2	1/2	0.33	3/4	1.58	3.70	2 1/4
10U-T10	5/8	5/8	0.46	15/16	1.34	3.92	2
12U-T12	3/4	3/4	0.58	1	1.17	4.11	1 15/16
16U-T16	1	1	0.76	1 1/4	1.30	4.48	2 9/16

Standpipe
(Straight) Tube



SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	TUBE SIZE (IN.)	THREAD SIZE (IN.)	BORE (IN.)	"E" NUT HEX SIZE (IN.)	"F" STEM HEX SIZE (IN.)	"A" COUPLING LENGTH (IN.)	CUT-OFF (IN.)
06U-06L	3/8	3/8	3/8 - 19	0.25	11/16	7/8	2.66	1 1/4
08U-08L	1/2	1/2	1/2 - 14	0.36	13/16	1 1/16	2.79	1 3/8
10U-12L	5/8	3/4	3/4 - 14	0.48	1	1 5/16	3.52	1 9/16
12U-12L	3/4	3/4	3/4 - 14	0.61	1	1 5/16	3.85	1 3/4
16U-16L	1	1	1 - 11	0.81	1 1/4	1 5/8	4.13	1 15/16

Female JIS
30° Flare Swivel

