

AIR CONDITIONING HOSE

AIR CONDITIONING

Air Conditioning Hose

Goodyear Galaxy G4826 - Recommended for R134a and R12 refrigerants in automotive, heavy-duty truck, construction and agricultural air conditioning systems. Meets or exceeds the performance requirements of SAEJ2064, Type C Class II.



TUBE: Black synthetic rubber (Chloroprene - Type A).

BARRIER: Nylon

REINFORCEMENT: Two layers of spiral polyester.

COVER: Black synthetic rubber (EPDM).

TEMPERATURE RANGE: -22°F to +257°F (-30°C to +125°C).

RB&H #	HOSE I.D. (IN.)	HOSE O.D. (MAX.)	SPECIFICATIONS			
			MAX. WORKING	MIN. BURST	WEIGHT PER (FT.)	REEL LENGTH (FT.)
AC-6	5/16	.75	500	2,000	.20	340
AC-8	13/32	.91	500	2,000	.28	235
AC-10	1/2	1.00	500	2,000	.33	210
AC-12	5/8	1.13	350	1,750	.38	175

BEADLOCK FITTINGS

Ferrules



RB&H #	SPECIFICATIONS
	HOSE SIZE
FMF06-25	6
FMF08-25	8
FMF10-25	10
FMF12-25	12

Green Orings

for R12 and R134a Hose



RB&H #	SPECIFICATIONS	
	DIA. (IN)	THICKNESS (IN)
AC4041	.301	.70
AC4042	.426	.70
AC4043	.551	.70
AC4044	.676	.70
AC4046	.364	.70