

BRASS FITTINGS

ROAD RANGER™

**Road Ranger™
Transmission Fitting for 1/8" & 5/32" Nylon Tubing**

**Collet
(slotted sleeve)**



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)
P60X2	1/8
P60X2.5	5/32

Male Elbow



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)	MALE PIPE (IN.)
P69X2X1	1/8	1/16
P69X2	1/8	1/8
P69X2.5	5/32	1/8

Nut



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)
P61X2	1/8
P61X2.5	5/32

Tube Insert



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)
PIX2	1/8
PIX2.5	5/32

Union



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)
P62X2	1/8
P62X2.5	5/32

Male Connector



SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)	MALE PIPE (IN.)
P68X2X1	1/8	1/16
P68X2	1/8	1/8
P68X2.5	5/32	1/8
P68X2.5X1	5/32	1/16

Road Ranger Kit



SPECIFICATIONS

RB&H #	DESCRIPTION	QTY.
P60X2	Slotted Sleeve	50
P62X2	Tube Union	20
P68X2	Male Connector	10
P68X2X1	Male Connector	10
P69X2	Compression Elbow	10
P69X2X1	Compression Elbow	10
NT10002BK	1/8" Black Nylon Tubing	100

See Tubing for "Nylon Airbrake Tubing" page 412

Transmission Fittings and Tubing assortment

PART # ROAD-RANGER-KIT

BRASS AIRBRAKE FITTINGS - SLEEVE TYPE

Brass Airbrake Fittings - Sleeve Type

Use with SAE J1402 Type A Rubber Airbrake Hose

**Airbrake Rubber Hose
SAE J1402
Type A
(DOT A1)**

SPECIFICATIONS

RB&H #	HOSE I.D. (IN.)	HOSE O.D. (IN.)
AIRBRAKE-6	3/8	3/4
AIRBRAKE-8	1/2	7/8

125 psi Working psi
900 psi Burst



ASSEMBLY INSTRUCTIONS:

- Slide nut and sleeve onto hose. Make sure bevel edge of sleeve faces out towards fitting
- Push hose into fitting until it bottoms
- Tighten nut down all the way

Connector



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	MALE PIPE (IN.)
RB&H #	REFERENCE #		
H38CX6X4	W15540	3/8	1/4
H38CX6X6	W24887	3/8	3/8
H38CX6X8	W15539	3/8	1/2
H48CX8X6	W33883	1/2	3/8
H48CX8X8	W33884	1/2	1/2

Connector with Spring Guard



SPECIFICATIONS

PRODUCT I.D.		HOSE I.D. (IN.)	MALE PIPE (IN.)
RB&H #	REFERENCE #		
H38CSX6X4	W15536	3/8	1/4
H38CSX6X6	W23907	3/8	3/8
H38CSX6X8	W15535	3/8	1/2
H48CSX8X6	W33885	1/2	3/8
H48CSX8X8	W33886	1/2	1/2