

INDUSTRIAL HOSE & FITTINGS

HOSE

SPECIFICATIONS

I.D. (IN.)	RB&H #	O.D. (IN.)	WEIGHT (LBS./FT.)	PSI	LENGTH (FT.)
	PVC-VF/S-1-1/2	1.67	.197	90	300
2	PVC-VF/S-2	2.21	.283	80	300
2 1/2	PVC-VF/S-2-1/2	2.68	.310	55	300
3	PVC-VF/S-3	3.20	.393	55	300
4	PVC-VF/S-4	4.26	.550	50	300
6	PVC-VF/S-6	6.26	.883	35	300

Blue Layflat Water Discharge

APPLICATION: General Purpose
 TUBE: Blue PVC compound
 COVER: Blue PVC compound
 TEMPERATURE: 0°F - 150°F
 COUPLINGS: Pin lug, cam & groove, king combination.

Blue Layflat Discharge Hose Assemblies

SINGLE BAND ASSEMBLIES SIZES 3/4" - 1 1/2"

DOUBLE BAND ASSEMBLIES SIZES 2" - 4"

Cam & Groove Aluminum
 FEMALE X FEMALE (TYPE C TO TYPE C)

King Combination
 MALE PIPE X MALE PIPE

SPECIFICATIONS

I.D. (IN.)	RB&H # 25' ASSEMBLY	RB&H # 50' ASSEMBLY
1 1/2	PVCBL-1-1/2-CCX25	PVCBL-1-1/2-CCX50
2	PVCBL-2-CCX25	PVCBL-2-CCX50
3	PVCBL-3-CCX25	PVCBL-3-CCX50
4	PVCBL-4-CCX25	PVCBL-4-CCX50

SPECIFICATIONS

I.D. (IN.)	RB&H # 25' ASSEMBLY	RB&H # 50' ASSEMBLY
1 1/2	PVCBL-1-1/2-STCX25	PVCBL-1-1/2-STCX50
2	PVCBL-2-STCX25	PVCBL-2-STCX50
3	PVCBL-3-STCX25	PVCBL-3-STCX50
4	PVCBL-4-STCX25	PVCBL-4-STCX50

Cam & Groove Aluminum
 FEMALE X MALE (TYPE C TO TYPE E)

Pin Lug Short Shank
 FEMALE X MALE
 (STRAIGHT THREADS)

SPECIFICATIONS

I.D. (IN.)	RB&H # 25' ASSEMBLY	RB&H # 50' ASSEMBLY
1 1/2	PVCBL-1-1/2-CEX25	PVCBL-1-1/2-CEX50
2	PVCBL-2-CEX25	PVCBL-2-CEX50
3	PVCBL-3-CEX25	PVCBL-3-CEX50
4	PVCBL-4-CEX25	PVCBL-4-CEX50

SPECIFICATIONS

I.D. (IN.)	RB&H # 25' ASSEMBLY	RB&H # 50' ASSEMBLY
1 1/2	PVCBL-1-1/2-BASX25	PVCBL-1-1/2-BASX50
2	PVCBL-2-BASX25	PVCBL-2-BASX50
3	PVCBL-3-BASX25	PVCBL-3-BASX50
4	PVCBL-4-BASX25	PVCBL-4-BASX50

INDUSTRIAL HOSE & FITTINGS

HOSE

**Mill Discharge
Hose Assemblies**



SPECIFICATIONS					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1 1/2	MILL50-1-1/2	1.69	200	20	50
2 1/2	MILL50-2-1/2	2.88	200	40	50

APPLICATION: Water pump discharge or washdown service.
Not recommended for fire fighting.

TUBE: Black rubber tube

COVER: Woven synthetic mildew resistant jacket.

TEMPERATURE: -40°F to 180°F

COUPLINGS: Pin lug (fire thread), adapters & nozzles

Steam Hose



SPECIFICATIONS					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1/2	SH-450-250-1/2	62/64	250	.33	50
3/4	SH-450-250-3/4	1 16/64	250	.49	50
1	SH-450-250-1	1 32/64	250	.61	50
1 1/4	SH-450-250-1-1/4	1 52/64	250	.83	50
1 1/2	SH-450-250-1-1/2	2 9/64	250	1.03	50

APPLICATION: Recommended for cleaning, thawing, blowout service, steam pumps.

TUBE: Black synthetic rubber

REINFORCEMENT: Spiral plied steel wire.

COVER: Black synthetic rubber.

TEMPERATURE: 0°F to 406°F

COUPLINGS: Must use ground joint swivels.

SAFETY ALERT

Ag Spray Economical

BLACK BLENDED EPDM TUBE AND COVER



SPECIFICATIONS					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1/4	AGSPRAY-1/4	.523	200	.11	500
3/8	AGSPRAY-3/8	.649	200	.15	500
1/2	AGSPRAY-1/2	.787	200	.19	500
5/8	AGSPRAY-5/8	.905	200	.24	500
3/4	AGSPRAY-3/4	1.063	200	.33	500
1	AGSPRAY-1	1.315	200	.42	500

APPLICATION: Agricultural chemical, water, and general service.

TUBE: Synthetic rubber, RMA Class C oil resistant

REINFORCEMENT: 2 fabric

COVER: Black synthetic rubber.

TEMPERATURE: -40°F to 190°F

COUPLINGS: Hose barb with clamps