

**INDUSTRIAL HOSE & FITTINGS**

**HOSE**

**Farm Tank Hose Assemblies**



APPLICATION: Dispensing gasoline, kerosene, and petroleum oils from farm and barrel type pumps.

COVER: Black synthetic rubber (ORS).

TUBE: Synthetic rubber (ORS).

REINFORCEMENT: Spiral synthetic Yarn (with static wire)

COUPLINGS: Male pipe thread.

**SPECIFICATIONS**

| I.D. (IN.) | RB&H #            | O.D. (IN.) | WEIGHT (LBS./FT.) | LENGTH (FT.) |
|------------|-------------------|------------|-------------------|--------------|
| 3/4        | AGGAS-3/4X10/WIRE | 1 1/8      | .27               | 10           |
| 3/4        | AGGAS-3/4X12/WIRE | 1 1/8      | .27               | 12           |
| 3/4        | AGGAS-3/4X14/WIRE | 1 1/8      | .27               | 14           |
| 1          | AGGAS-1X10/WIRE   | 1 3/8      | .50               | 10           |
| 1          | AGGAS-1X12/WIRE   | 1 3/8      | .50               | 12           |
| 1          | AGGAS-1X14/WIRE   | 1 3/8      | .50               | 14           |

**Nitrile Hose**

WATER, CHEMICALS, MARINE, HYDRAULIC, PETROLEUM

APPLICATIONS

APPLICATION: Automotive, general purpose, industrial and marine applications where flexibility and kink resistance are important.

COVER & TUBE: Nitrile black. Offers excellent oil, ozone, weather, and abrasion resistance, Helix wire crush resistant. Sizes 7/8"-2" sold in 5', 10', 25', or 50' increments. Sizes 3"-4" sold in 5' or 10' increments.

TEMPERATURE: -40°F to 200°F

**SPECIFICATIONS**

| I.D. (IN.) | RB&H #      | O.D. (IN.) | PSI | WEIGHT (LBS./FT.) | ON DISPLAY |
|------------|-------------|------------|-----|-------------------|------------|
| 7/8        | 68-5-7/8    | 1 5/32     | 32  | 0.30              | *          |
| 1          | 68-5-1      | 1 9/32     | 28  | 0.40              | *          |
| 1 1/8      | 68-5-1-1/8  | 1 13/32    | 25  | 0.40              | *          |
| 1 1/4      | 68-5-1-1/4  | 1 17/32    | 24  | 0.50              | *          |
| 1 5/16     | 68-5-1-5/16 | 1 5/8      | 23  | 0.50              | *          |
| 1 3/8      | 68-5-1-3/8  | 1 11/16    | 22  | 0.50              | *          |
| 1 1/2      | 68-5-1-1/2  | 1 13/16    | 20  | 0.60              | *          |
| 1 5/8      | 68-5-1-5/8  | 1 15/16    | 18  | 0.60              | *          |
| 1 3/4      | 68-5-1-3/4  | 2 1/16     | 17  | 0.70              | *          |
| 1 7/8      | 68-5-1-7/8  | 2 3/16     | 16  | 0.70              | *          |
| 2          | 68-5-2      | 2 5/16     | 15  | 0.80              | *          |
| 3          | 68-5-3      | 3 5/16     | 20  | 1.20              |            |
| 4          | 68-5-4      | 4 5/16     | 16  | 1.60              |            |

**Nitrile Display**

RB&H PART #: NITRILE-DISPLAY



FEATURES:

- 11 hose sizes from 7/8" to 2"
- Labeled, wall mounted rack.
- Sign & 22 hangers for hose.

**Fuel Line Hose**

FEATURES/BENEFITS:

- Fuel line, vapor emission, and crankcase ventilation. Nitrile tube and hypalon cover to withstand grease, oil abrasion, and high temperatures under the hood.
- Ozone resistant.
- Meets SAE 30R7 specifications.
- 25' spools.
- Not for fuel injector application



**SPECIFICATIONS**

| I.D. (IN.) | RB&H #  | APPROXIMATE WEIGHT (LBS.) |
|------------|---------|---------------------------|
| 1/4        | GL1425  | 3                         |
| 5/16       | GL51625 | 4                         |
| 3/8        | GL3825  | 5                         |