

INDUSTRIAL HOSE & FITTINGS

TUBING

Braided Reinforced PVC Tubing



APPLICATION: Pneumatic, air, water, glue, lubrication, air, VACUUM lines, drain lines.

TUBE: Clear with polyester mesh braiding, non-toxic ingredients, FDA standards, corrosion & abrasion resistant.

TEMPERATURE: 25°F to 150°F

COUPLINGS: Clamped hose barbs.

SPECIFICATIONS

I.D. (IN.)	RB&H #	O.D. (IN.)	WALL (IN.)	PSI	WEIGHT (LBS./FT.)	LENGTH (FT.)
3/16	PVTL-3/16	.394	.103	315	.0506	100
1/4	PVTL-1/4	29/64	.102	300	.0603	100
5/16	PVTL-5/16	17/32	3/32	280	.0777	100
3/8	PVTL-3/8	.600	.113	230	.0926	100
1/2	PVTL-1/2	.728	.114	215	.1182	100
5/8	PVTL-5/8	29/32	9/64	200	.1817	100
3/4	PVTL-3/4	1.024	.137	150	.2053	100
1	PVTL-1	1.299	.150	130	.2903	100
1 1/4	PVTL-1-1/4	1.732	.241	110	.6070	100
1 1/2	PVTL-1-1/2	1.929	.215	70	.6212	100
2	PVTL-2	2 1/2	1/4	50	.9502	100

Clear PVC Tubing



APPLICATION: Air, drain lines, water, weak chemicals.

TUBE: Glass like clarity, PVC compound meets USP class VI requirements. Conforms to the FDA, USDA standards, listed NSF 51, light weight, abrasion resistant, USA made.

COUPLINGS: Clamped hose barbs.

SPECIFICATIONS

I.D. (IN.)	RB&H #	O.D. (IN.)	WALL (IN.)	PSI	WEIGHT (LBS./FT.)	LENGTH (FT.)
1/8	PT20004NA	1/4	1/16	68	.021	100
3/16	PT20005NA	5/16	1/16	55	.027	100
1/4	PT20006NA	3/8	1/16	55	.034	100
1/4	PT20000NA	1/2	1/8	70	.083	100
5/16	PT20007NA	7/16	1/16	50	.042	100
3/8	PT20008NA	1/2	1/16	40	.048	100
3/8	PT20001NA	9/16	3/32	50	.078	100
3/8	PT20009NA	5/8	1/8	65	.111	100
1/2	PT20010NA	5/8	1/16	30	.062	100
1/2	PT20011NA	3/4	1/8	45	.139	100
5/8	PT20014NA	7/8	1/8	40	.166	100
3/4	PT20016NA	1	1/8	35	.194	100
1	PT20020NA	1 1/4	1/8	28	.250	100
1 1/4	PT20024NA	1 5/8	3/16	31	.478	50