

INDUSTRIAL HOSE & FITTINGS

COUPLINGS/CLAMPS

Air/Water Couplings

**“Air King”
Universal Couplings**

Malleable iron couplings rated 110psi at ambient temperature 70°f. Standard Air King couplings come with AWR4 washers. (JDQI)



RUBBER WASHERS: Same size for all coupling sizes.

TEMPERATURE RANGE: -20°F to 160°F

SPECIFICATIONS

| | Hose Ends | Male NPT Ends | Female NPT Ends | 2 Bolt Clamp |
|-----|-----------|---------------|-----------------|--------------|
| | | AMB-11/D | AMC-11/D | |
| NPT | RB&H # | RB&H # | RB&H # | RB&H # |
| 3/8 | AMH/D | AMB/D | AMC/D | CD/D |
| 1/2 | AM-1/D | AM-2/D | AM-3/D | A-4/D |
| 3/4 | AM-6/D | AM-7/D | AM-8/D | A-9/D |
| 1 | AM-11/D | AM-12/D | AM-13/D | A-14/D |

Industrial Clamps

**Double Bolt Clamps
With Two Saddles**



**Oetiker Double
Ear Clamps**



SPECIFICATIONS

| RB&H # | O.D. FROM | O.D. TO | TORQUE |
|--------|-----------|---------|--------|
| 400/D | 3 32/64 | 3 52/64 | 40 |
| 463/D | 4 2/64 | 4 18/64 | 40 |
| 525/D | 4 16/64 | 4 60/64 | 60 |
| 550/D | 4 32/64 | 5 16/64 | 60 |
| 600/D | 5 9/64 | 5 44/64 | 60 |
| 675/D | 5 60/64 | 6 32/64 | 60 |
| 769/D | 6 32/64 | 7 36/64 | 60 |
| 818/D | 7 44/64 | 8 12/64 | 125 |
| 988/D | 8 60/64 | 9 56/64 | 125 |

SPECIFICATIONS

| RB&H # | SIZE (IN.) | CLOSED | OPEN |
|--------|------------|--------|-------|
| CC-3 | 3/16 | 0.118 | 0.197 |
| CC-4 | 1/4 | 0.197 | 0.276 |
| CC-5 | 5/16 | 0.276 | 0.354 |
| CC-6 | 3/8 | 0.315 | 0.433 |
| CC-8 | 1/2 | 0.433 | 0.512 |
| CC-9 | 9/16 | 0.512 | 0.591 |
| CC-10 | 5/8 | 0.591 | 0.708 |
| CC-12 | 3/4 | 0.669 | 0.787 |
| CC-13 | 13/16 | 0.748 | 0.866 |
| CC-14 | 7/8 | 0.787 | 0.905 |
| CC-15 | 15/16 | 0.866 | 0.984 |
| CC-16 | 1 | 0.905 | 1.063 |
| CC-18 | 1 1/8 | 1.063 | 1.220 |
| CC-23 | 1 7/16 | 1.339 | 1.457 |
| CC-24 | 1 1/2 | 1.457 | 1.575 |

*Assortments on page 464.