

TUBING

STEEL

STANDARD UPS LENGTH: 20' (2 - 7' pieces), (1 - 6' piece). 20' continuous lengths available.
 TEMPERATURE RANGE: -65°F to +500°F.
 ADDITIONAL INFORMATION: Packaging charge applicable for 20' motor freight lengths.
 Also available in plated steel or different wall thickness.

Steel Hydraulic Tubing



Tube bending available.
 Call for pricing.

SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)	WALL THICKNESS (IN.)
03ST	3/16	.035
04ST	1/4	.035
05ST	5/16	.035
06ST	3/8	.035
06ST-065	3/8	.065
08ST	1/2	.049
08ST-065	1/2	.065
10ST	5/8	.049
12ST	3/4	.065
16ST	1	.065

Meets SAE J525 specifications
 Custom bending & assemblies available

TEMPERATURE RANGE: -425°F to +1200°F.
 ADDITIONAL INFORMATION: Packaging charge applicable for 20' motor freight lengths.

Stainless Steel Hydraulic Tubing

SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)	WALL THICKNESS (IN.)
06SST	3/8	.035
08SST	1/2	.035
05SST X .028	5/16	.028

Meets ASTM 269 specifications

COPPER

STANDARD LENGTH: 50'.
 APPLICATIONS: Refrigeration.

Copper Tubing
 SOFT WALL



Tube bending available.
 Call for pricing.

SPECIFICATIONS

RB&H #	TUBE O.D. (IN.)
02CTR	1/8
03CTR	3/16
04CTR	1/4
05CTR	5/16
06CTR	3/8
08CTR	1/2
10CTR	5/8
12CTR	3/4

Meets SAE J528 specifications