



## Fastener Part Numbering System

Example  
Part #:

4C200HCS5P

4 Diameter	C Thread	200 Length	HCS Type		5 Grade	P Material
# = -1/4"	C = Course	34 = 3/4"	HCS	Hex Cap Screw	5	P = plain finish
4 = 1/4"	F = Fine	12 = 1/2"	CB	Carriage Bolt	8	-4 = 18-8 Stainless Steel
5 = 5/16"		78 = 7/8"	HLS	Hex Lag Screw	2	-3 = T316 Stainless Steel
6 = 3/8"		100 = 1"	PB	Plow Bolt		-6 = Brass
7 = 7/16"		114 = 1-1/4"	SCS	Socket Cap Screw		-7 = Silicone Bronze
8 = 1/2"		112 = 1-1/2"	FSCS	Flat Socket Cap Screw		-9 = Nylon
9 = 9/16"		134 = 1-3/4"	BSCS	Button Socket Cap Screw		-0 = Aluminum
10 = 5/8"		200 = 2"	SSS	Socket Shoulder Screw		
12 = 3/4"		214 = 2-1/4"	SS	Socket Set Screw		
16 = 1"		212 = 2-1/2"	LA	Long Arm Hex Key		
20 = 1-1/4"		234 = 2-3/4"	SA	Short Arm Hex Key		
24 = 1-1/2"		300 = 3"	HN	Hex Nut		
32 = 2"		314 - 3-1/4"	HMSN	Hex Machine Screw Nut		
		312 = 3-1/2"	NYL	Nylon Insert Locknut		
		334 = 3-3/4"	HJN	Hex Jam Nut		
		400 = 4"	RCHN	Rod Coupling Hex Nut		
		412 = 4-1/2"	FWN	Forged Wing Nut		
		500 = 5"	HCN	Hex Castle Nut		
		512 = 5-1/2"	SHN	Slotted Hex Nut		
		600 = 6"	HHN	Heavy Hex Nut		
			HH2H	Heavy Hex Nut 2-H		
			SFLN	Serrated Flange Locknut		
			AN	Acorn Nut		
			TW	Toggle Wing		
			AMLC	Allmetal Lock Nut Grade C		
			RSMS	Round Slotted Machine Screw		
			FSMS	Flat Slotted Machine Screw		
			PSAT	Pan Slotted Type AB Tapping Screw		
			HWSAT	Hex Washer Slotted Type AB Tapping Screw		
			HWTEK	Hex Washer Tek Screw		
			PPAT	Pan Phillips Type AB Tapping Screw		
			FLST	Standard Flatwasher		
			FLSA	SAE Flatwasher		
			LWR	Standard Lockwasher		
			FLA3	Flatwasher A-325		
			BWMA	Bevel Washer Malleable		
			FEWA	Fender Washer		
			EXTW	External Tooth Lockwasher		
			INTW	Internal Tooth Lockwasher		
			DP	Dowel Pin		
			TP	Tension Pin (spring, roll)		
			CP	Cotter Pin		